# SHEAR STRENGTH OF UNSATURATED EXPANSIVE SOILS FROM QUEENSLAND NATURAL SLOPES

\* Tharindu Abeykoon<sup>1</sup> and Jessica Trofimovs<sup>2</sup>

<sup>1,2</sup>Science and Engineering Faculty, Queensland University of Technology, Australia

\*Corresponding Author, Received: 30 Nov. 2020, Revised: 19 Jan. 2021, Accepted: 07 Mar. 2021

**ABSTRACT:** Expansive soils exhibit significant changes in their swell and shrink behaviour upon variation of moisture content. The majority of soils in Queensland are expansive; consequently, failures in natural slopes with expansive characteristics are commonly reported under climate-induced soil moisture variations. In order to understand the failure mechanism of such soil slopes, it is vital to analyse slope stability under unsaturated conditions. The current study employed undisturbed soil samples from natural slopes in Queensland and determined their basic soil properties, including the soil-water characteristic curve (SWCC), and unsaturated shear strength to facilitate the analysis of rainfall-induced slope failure. A series of conventional direct shear tests were conducted for different moisture contents under various vertical stresses. The test results were analysed to obtain the variation of the apparent cohesion and the effective friction angle of the soil with moisture content and suction. The study presents an empirical equation to predict the cohesive component in the shear strength of unsaturated expansive soils as an exponential function of suction. The formulation originated from multiple linear regression analyses for data sets obtained from shear tests using undisturbed soils with varying moisture contents. The empirical equations can realistically predict the reduction in soil cohesion due to wetting ( $R^2 = 0.8666$ ). The study provides an alternative to the quantitative estimation of unsaturated shear strength of expansive soils.

Keywords: Unsaturated soil, Unsaturated shear strength, Expansive soil, Slope stability, Direct shear test

#### **1. INTRODUCTION**

Geotechnical site investigation is of prime importance in ensuring the safety of civil engineering structures related to embankments, pavements and landfills [1-14]. Therefore the understanding of the soil interface shear strength is vital in designing and analysing the stability of geotechnical structures [15-20]. The cohesive strength of unsaturated soils plays an important role in the stability of soil slopes [17, 21-25], in which the reduction of the soil cohesion due to wetting can cause shear deformation of the slopes at a previously unsaturated shallow layer. Therefore, the determination of the critical condition for sliding requires a slope stability analysis, including an effect for the loss of cohesion.

As shear strength tests on unsaturated soils are costly and time-consuming, simple and indirect methods have been developed to obtain the shear strength of unsaturated soils for engineering purposes. Numerous researches suggest that the shear strength of unsaturated soils can be predicted using different equations [26]. Basically, two primary approaches are used in predicting the unsaturated shear strength of soil; effective and independent stress approaches [27, 28]. Therefore researchers have developed not only theoretical but also empirical approaches to estimate unsaturated shear strength of soil, including the establishment of the non-linear behaviour of cohesion in unsaturated expansive soils, analytical SWCC based approach and the determination of cohesion using hyperbolic equations [26, 29-31]. However, no compelling attempts are made on the analysis of the characteristics of unsaturated shear strength and the relationship between the shear strength parameters and suction of unsaturated expansive soils in the Queensland region.

This paper presents an empirical equation for the prediction of unsaturated shear strength of expansive soils from natural slopes in Queensland. Due to the tropical weather conditions and the expansive nature of Queensland soils, the determination of shear strength of Queensland soils is of prime importance to mitigate adverse impacts on engineering structures [4]. In this regard, a series of direct shear tests on unsaturated soils from natural slopes in Maleny, Queensland, Australia was conducted. Direct shear testing of unsaturated soils is desirable since less time is required to reach the failure of the soil specimen compared to the triaxial test. The time to failure in the direct shear test is significantly reduced because the specimen is relatively thin. However, a lengthy testing period is expected for unsaturated soils due to the low coefficient of permeability of the soil. In this paper, an empirical equation is suggested for the prediction of unsaturated shear strength as a function of suction.

The equation was obtained from a multiple linear regression analysis of direct shear tests using undisturbed expansive soils with varying moisture contents. Even though the equation lacks theoretical validity from a physical standpoint, it has practical advantages, especially for geotechnical engineering purposes.

# 2. STUDY AREA

The study area is located in the Lake Baroon catchment, Maleny, Queensland, Australia (26.72 °S 152.87 °E), situated on Mapleton - Maleny plateau, which has been documented as a highly susceptible area for rainfall-induced slope failures since the mid - 1950s. (e.g. [32]). Slope failures and mass movements of sediment into the waterways within the Lake Baroon catchment are recognised as a significant risk to water quality and the water storage capacity of Lake Baroon, which is used to supply water to South East Queensland. Approximately 170 mass movement landforms have been identified within the catchment, and the study area is one such high-risk slope. This landslide site hosted a voluminous, single-failure rotational landslide in 2008 following heavy rainfall.

### 3. TEST MATERIAL

The test series herein employed soils from the Lake Baroon catchment. Undisturbed samples from seven locations of the study area were collected at various depths ranging from the surface down to 4 m. Initially, a trench was created with an excavator to the desired depth and then 500 mm long sampling tubes (diameter 75 mm) were inserted into the soil by connecting a specially modified adaptor to the excavator's arm, as in Fig. 1.



Fig. 1 Insertion of soil sampling tube by the modified adaptor to the excavator's arm

Table 1 summarises the results of the laboratory tests conducted to determine the index properties of the soil according to Australian standards.

Table 1 Index soil properties

Classification Test	Results		
Carlin alex Distribution	% finer than 75 $\mu$ m > 84%		
Grain size Distribution	Clay % = 50.7 %		
Atterberg Limits	LL = 67.2 %		
	PI = 28.8 %		
Linear Shrinkage	LS = 13.4 %		
Specific Gravity	$G_{s} = 2.68$		
X-ray diffraction	Presence of Smectite		
(XRD)	minerals (> 30 %)		
Note: II - Liquid limit: DI - Diastia index: IS -			

Note: LL = Liquid limit; PI = Plastic index; LS = Linear shrinkage

#### 4. TEST PROCEDURE

Undisturbed soil samples were collected from the Lake Baroon catchment. Soil sampling tubes were employed in collecting undisturbed samples from seven locations at various depths. In-situ density and the moisture content of soil were determined for each sampling location. The soil samples were used to determine the SWCC, swelling characteristics and unsaturated shear strength.

A dewpoint potentiometer (Fig. 2) was employed in determining the SWCC, which is the graphical relationship between soil suction and water content (gravimetric or volumetric) or degree of saturation. The dewpoint potentiometer measures water potential from 0 to -300 MPa with an accuracy of  $\pm 0.1$  MPa from 0 to -10 MPa and  $\pm 1$  % from -10 to -300 MPa. The high total suctions measured from the WP4C Dewpoint potentiometer were assumed to consist of negligible osmotic suction effect and hence, used as matric suction. These samples were initially prepared for known water contents and placed in enclosed containers to prevent any moisture loss prior to testing. Further, to obtain the SWCC, a best fitting relationship was established using the logarithmic model proposed by Fredlund and Xing [33] as presented in Eq. (1) and (2).



Fig. 2 WP4C Dewpoint potentiometer for suction measurement

$$\theta(\psi, a, n, m) = \frac{C(\psi) \theta_s}{\{\ln [2.718 + (\frac{\psi}{a})^n]\}^m}$$
(1)

$$C(\psi) = \frac{-\ln(1+\frac{\psi}{\psi_r})}{\ln(1+10^6/\psi_r)} + 1$$
(2)

where a is equal to the air-entry suction; n is the tangent to the curve at the inflexion point (in the transition zone); m is related to the residual water content;  $C(\psi)$  is a correction function;  $\psi_i$  is the suction corresponding to a given water content, and  $\theta_s$  is the saturated volumetric water content.



Fig. 3 Conventional oedometer apparatus used for the shear rate determination

A series of oedometer based one-dimensional consolidation tests (Fig. 3) were conducted as prescribed in AS 1289.6.6.1-1998 for soil samples under different surcharges to determine the rate of shearing for each direct shear test. At the completion of the primary consolidation, the time to reach 50% consolidation (t<sub>50</sub>) and the following empirical equations were used to determine the shearing rate (Eq. (3) and (4)). Taylor's square root of time fitting method was used to determine  $t_{50}$ during the study. The selected surcharge values for this study were 50, 100, 150, 200 and 250 kPa. Samples were tested for different initial volumetric water contents from 25% to 43% to replicate in-situ water contents. The samples were cured for four days prior to the oedometer tests. The soil samples prepared for known initial gravimetric moisture contents were then statically compacted to achieve the target density to replicate in-situ density. Subsequently, a representative sample was cut into a consolidation ring, followed by the placement of filter papers and porous disks at the top and the bottom of the sample. The samples were then subjected to the aforementioned surcharges.

$$t_f = 50t_{50}$$
(3)

$$R = d_P / t_f \tag{4}$$

where  $t_f$  is the time to failure in minutes,  $d_p$  the shear displacement at which peak strength is likely to be reached, in millimetres, and R is the required shearing rate.

To obtain cohesion (c) and friction angle ( $\varphi'$ ) for various in-situ water contents of soil, five direct shear tests for each water content were conducted on five identical soil samples (the same density and water content) with variation in the normal stresses 50, 100, 150, 200 and 250 kPa as prescribed in AS 1289.6.2.2 - 1998. The maximum failure shear stresses were then plotted with the corresponding normal stress to obtain c and  $\varphi'$  for the given water content. The shearing rate determined from the oedometer tests were adopted for the direct shear tests. The same procedure was repeated for five different water contents to replicate in-situ water content values.

The direct shear apparatus (Fig. 4) accommodated samples with a diameter of 63.5 mm and a height of 25 mm. The soil samples prepared for the predetermined initial moisture contents were statically compacted to achieve the target density. Subsequently, a representative sample was cut into a shear ring, as shown in Fig. 4, followed by the placement of filter papers and porous disks at the top and the bottom of the sample.

After determining c and  $\varphi'$  for different water contents, using the SWCC, which was measured for the same density, the suction corresponding to the volumetric water content was obtained, and ultimately the variation of c with the suction was adopted to determine  $\varphi^{b}$ .



Fig. 4 Direct shear apparatus and the soil sample compacted into the cutting ring for direct shear test

### 5. RESULTS AND DISCUSSION

#### 5.1 The SWCC

The total suction  $(\psi)$  was measured based on the relative humidity concept and the SWCC equation proposed by Fredlund and Xing [33] that was used in this study. However, due to the negligible osmotic suction, the total suctions were assumed as the matric suctions. Figure 5 depicts the SWCC for the test material.

The air-entry suction is approximately 85 kPa, and the residual degree of saturation 8.2%. The SWCC is clearly step-phased with the boundary effect zone and the transition zone well defined, while the residual zone is not well defined. In the boundary effect zone, the soil is almost saturated, and the water content is nearly independent of suction, while the shear strength develops linearly with suction. In the transition zone, the water content decreases drastically as the suction increases, and the shear strength varies nonlinearly with suction. In the residual zone, the water content has a residual value. For sandy and silty soils, the shear strength is independent of suction; by contrast, for clayey soils, it increases slightly with the suction increase [26].



Fig. 5 The SWCC for the test material

#### 5.2 Shearing Rate

The  $t_{50}$  determined using Taylor's square root of time fitting method was adopted in calculating the shearing rate. Initially, a compression vs square-root-of-time plot was produced, as depicted in Fig. 6. Figure 6 presents the compression vs square-root-of-time plots for normal stresses 50, 100, 150, 200 and 250 kPa. The construction as prescribed in AS 1289.6.6.1-1998 was then employed in determining the shearing rates (Table 2).

# **5.3 Direct Shear Tests**

Direct shear tests were conducted for all five moisture contents under the same normal stresses 50, 100, 150, 200 and 250 kPa. Figure 7 presents the variation of shear stress with horizontal displacement for the soil specimens with the volumetric water content of 34.6%. Figure 7 depicts that the peak shear stresses increased with normal stress, and curves are clearly step-phased. In the beginning, the shear stress increases very rapidly with the increase of shear displacement. Then, after a certain stress value, the slope of the curve declines. It also suggests that when the normal stresses increase from 50 to 250 kPa, the stress-strain relationship of the specimen changes from strain-softening to strain-hardening.





Fig. 6 The compression versus square-root-of-time plot

Table 2 Shearing rates determined

Normal stress	t50 (min)	Shear rate
(kPa)	•50 (11111)	(mm/min)
50	2.601	0.15379
100	1.553	0.25757
150	2.357	0.16971
200	3.440	0.11628
250	1.496	0.25063



Fig. 7 Variation of shear stress with horizontal displacement under different normal stresses for the volumetric water content of 34.6%

#### 5.4 Shear Strength

The shear strength of the soils decreased with the increase in moisture content. Average volumetric water contents ranged from 0.25 to 0.43 for the test material (44.0 - 75.4% saturation). Figure 8 shows the results with a simple linear regression for each of the volumetric water content. Table 3 lists the values of the y-intercept and the inclination of the regression lines (i.e. cohesive strength and angle of shearing resistance in terms of simple linear regression), along with the corresponding suction values as per the Fredlund and Xing [33] fitting curve presented in Fig. 5.

The inclinations of the regression lines are largest in the drier conditions and decrease for the wetter samples, converging at  $16-18^{\circ}$  (Fig. 8; Table 3). In other words, the angle of shearing resistance of the moist soils seems to be constant, independent of volumetric water content, except in the drier condition.



Fig. 8 Results of the direct shear tests (The solid lines indicate the simple linear-regression lines for each specimen group)

 Table 3 Shear strength parameters obtained by

 simple linear regression with suction

Vol. water content (m <sup>3</sup> /m <sup>3</sup> )	Cohesion (kPa)	Friction angle (Degree)	Suction (kPa)
0.251	92.12	17.22	11258.7
0.319	79.34	18.06	4364.8
0.346	66.21	16.42	3043.5
0.385	54.96	16.33	1827.7
0.432	45.73	16.75	991.8

The y-intercepts of the regression lines decreased with increasing moisture content and approached a minimum value at the more saturated conditions (Table 3). Figure 9 shows the relationships between the corresponding suction values for the average volumetric water content in each group and the y-intercept of the regression lines. The values of the y-intercept tend to increase linearly on the semi-log scale (i.e. the cohesive strength of the soils exponentially increases with an increase in suction).

# 5.5 Formulation of Shear Strength as a Function of Suction

On the basis of the shear strength reduction characteristics (Figs. 8 and 9), it was assumed that: (1) the angle of shearing resistance takes a constant value; (2) an exponential function is valid to express the relationship between apparent cohesion and suction.



Fig. 9 Relationship between the corresponding suction values for the average volumetric water content and cohesive strength

From this, the regression function can be postulated as follows:

$$\tau = \sigma' \tan \varphi' + C e^{\mu \psi} \tag{5}$$

where  $\tau$  is shear strength,  $\sigma'$  is net normal stress,  $\psi$  is suction,  $\varphi'$  is the effective angle of shearing resistance, C is a hypothetical minimum value of cohesion (when  $\psi = 0$ ), and  $\mu$  is a coefficient related to the susceptibility of strength increment ( $\mu$ >0).



Fig. 10 Variation in the square of correlation coefficient of Eq. 6 with respect to the varied value of  $\phi^\prime$ 

To determine the values of unknowns (i.e.  $\phi'$ , C and  $\mu$ ), Eq. 5 should be linearised as in Eq. 6:

$$\ln \left[\tau - \sigma' \tan \varphi'\right] = \mu \psi + \ln C \tag{6}$$

Using the linearised Eq. 6, multiple regression analyses were conducted by considering arbitrary  $\varphi'$ . For arbitrary  $\varphi'$  values, simple linear regression analyses were conducted for data sets of ln [ $\tau - \sigma' \tan \varphi'$ ], and  $\psi$  to determine the  $\varphi'$  with the highest coefficient of determination, as shown in Fig. 10.



Fig. 11 The relationships between the logarithm of cohesive shear strength and suction

The shear strength of test material was well represented by the below regression function  $\tau = \sigma' \tan 16.85^{\circ} + 43.55 e^{1.02 \times 10^{-4} \psi}$  as depicted in Fig. 11 (R<sup>2</sup> = 0.8666). The regression variables in the equations include the liquefaction characteristics of the soils, effects of lubrication and susceptibility to changes in pore-water pressure during the shear deformation. For this reason, the values should be considered purely as empirical parameters for the soils, each of which has inherent geotechnical behaviours.

# 6. CONCLUSIONS

The cohesive strength of an unsaturated expansive soil was formulated as an exponential function of suction. In the formulation, shear expressed strength τ was as  $\tau = \sigma' \tan \varphi' + C e^{\mu \psi}$ ; where  $\sigma'$  is net normal stress,  $\phi'$  is the effective angle of shearing resistance, C is minimum cohesion, µ is a susceptibility coefficient, and  $\psi$  is suction of soil. An advantage of this formulation is that all the parameters required are available without any extensive soil testing. The variables can be obtained by a basic shear test and a subsequent regression analysis. It is considered that this empirical method provides a convenient alternative for engineering practice.

# 7. ACKNOWLEDGMENTS

The authors gratefully acknowledge the technical staff at Queensland University of Technology (QUT) for providing the laboratory facilities to conduct the test series. Further, gratitude should be extended to Steve Hackworth from THE SOILTESTERS for providing the inkind support for the project. Also, the authors appreciate SEQWater, Australia, for providing with site access. The first author acknowledges the scholarship for the doctoral degree received from QUT, Australia.

#### 8. REFERENCES

- Udukumburage, R. S., Gallage, C., Dawes, L. and Gui, Y. Determination of the hydraulic conductivity function of grey Vertosol with soil column test. Heliyon, 2020.
- [2] Weerasinghe, I., Gallage, C., Dawes, L. and Kendall, P. Factors affecting the hydraulic performance of a geosynthetic clay liner overlap. Journal of Environmental Management, 2020.
- [3] Suryo, E. A., Zaika, Y., Gallage, C. and Trigunarsyah, B. A Non-Destructive Method for Investigating Soil Layers of an Individual

Vulnerable Slope. International Journal of GEOMATE, Vol. 18, Issue 69, 2020, pp. 1-8.

- [4] Udukumburage, R. S., Gallage, C. and Dawes, L. Oedometer based estimation of vertical shrinkage of expansive soil in a large instrumeted soil column. Heliyon, Vol. 5, Issue 9, 2019.
- [5] Weerasinghe, I. A., Gallage, C. and Dawes, L. Optimising geosynthetic clay liner overlaps: implications on hydraulic performance. Environmental Geotechnics, 2019,pp. 1-10.
- [6] Jayakody, S., Gallage, C. and Ramanujam, J. Performance characteristics of recycled concrete aggregate as an unbound pavement material. Heliyon, Vol. 5, Issue 9, 2019.
- [7] Clark, B. R. and Gallage, C. Superior performance benefits of multigrade bitumen asphalt with recycled asphalt pavement additive. Construction and Building Materials, 2020.
- [8] Jayalath, C. P., Gallage, C., Dhanasekar, M., Dareeju, B. S., Ramanujam, J. and Lee, J. Pavement model tests to investigate the effects of geogrid as subgrade reinforcement, 2018.
- [9] Gallage, C. and Jayalath, C. Use of Particle Image Velocimetry (PIV) technique to measure strains in geogrids, 2019.
- [10] Cheah, C., Gallage, C., Dawes, L. and Kendall, P. Measuring hydraulic properties of geotextiles after installation damage. Geotextiles and Geomembranes, Vol. 45, Issue 5, 2017, pp. 462-470.
- [11] Clark, B. R., Gallage, C. and Yeaman, J. Temperature susceptibility of multigrade bitumen asphalt and an approach to account for temperature variation through deep pavements. International Journal of Urban and Civil Engineering, Vol. 12, Issue 6, 2018, pp. 712-717.
- [12] Gallage, C., Mostofa, G., Vosolo, D. and Rajapakse, J. A new laboratory model of a slaking chamber to predict the stability of onsite coal mine spoils. International Journal, Vol.10, Issue 22, 2016, pp. 2065-2070.
- [13] Souliyavong, T., Gallage, C., Egodawatta, P. and Maher, B. Factors affecting the stability analysis of earth dam slopes subjected to reservoir drawdown. The GEOMATE International Society, 2012.
- [14] Cheah, C., Gallage, C., Dawes, L. A. and Kendall, P. Effect of simulated rock dumping on geotextile, 2015.
- [15] Gallage, C. and Uchimura, T. Direct Shear Testing on Unsaturated Silty Soils to Investigate the Effects of Drying and Wetting on Shear Strength Parameters at Low Suction. Journal of Geotechnical and Geoenvironmental Engineering, Vol. 142, Issue 3, 2016.

- [16] Amarasinghe, M. P., De Silva, L. I. N. and Gallage, C. The effect of lateral confinement on the settlement characteristics of shallow foundations on sand. International Journal of GEOMATE, Vol. 15, Issue 51, 2018, pp. 258-265.
- [17] Gallage, C., Jayakody, S. and Uchimura, T. Effects of slope inclination on the rain-induced instability of embankment slopes. The GEOMATE International Society, 2012.
- [18] Gallage, C., Kodikara, J. and Uchimura, T. Laboratory measurement of hydraulic conductivity functions of two unsaturated sandy soils during drying and wetting processes. Soils and Foundations, Vol. 53, Issue 3, 2013, pp. 417-430.
- [19] Abeykoon, T., Udukumburage, R., Gallage, C. and Uchimura, T. Comparison of Direct and Indirect Measured Soil-Water Characteristic Curves for a Silty Sand. International Journal, Vol. 13, Issue 39, 2017, pp. 09-16.
- [20] Jayakody, S., Gallage, C. and Ramanujam, J. Effects of reclaimed asphalt materials on geotechnical characteristics of recycled concrete aggregates as a pavement material. Road Materials and Pavement Design, Vol. 20, Issue 4, 2019, pp. 754-772.
- [21] Suryo, E. A., Gallage, C. and Trigunarsyah, B. A method for predicting rain-induced instability of an individual slope. Queensland University of Technology, 2015.
- [22] Towhata, I., Uchimura, T. and Gallage, C. On Early Detection and Warning against Rainfall-Induced Landslides (M129). Springer Berlin Heidelberg, 2005.
- [23] Abeykoon, T., Gallage, C. and Trofimovs, J. Optimisation of sensor locations for reliable and economical early warning of rainfallinduced landslides. in Ninth International Conference on Geotechnique, Construction Materials and Environment (GEOMATE 2019), Japan, 2019, pp. 69-74.
- [24] Gallage, C., Dareeju, B., Trofimovs, J., Wang, L. and Uchimura, T. Real-time monitoring and failure prediction of a slope due to rainfall-case study, 2018.
- [25] Abeykoon, T., Gallage, C., Dareeju, B. and Trofimovs, J. Real-time monitoring and wireless data transmission to predict raininduced landslides in critical slopes. Australian Geomechanics Journal, Vol. 53, Issue 3, 2018, pp. 61-76.
- [26] Vanapalli, S., Fredlund, D., Pufahl, D. and Clifton, A. Model for the prediction of shear strength with respect to soil suction. Canadian Geotechnical Journal, 33, 3 (1996), 379-392.
- [27] Bishop, A. W. The principle of effective stress. Teknisk ukeblad, Issue 39, 1959, pp. 859-863.

- [28] Fredlund, D., Morgenstern, N. R. and Widger, R. The shear strength of unsaturated soils. Canadian geotechnical journal, Vol. 15, Issue 3, 1978, pp. 313-321.
- [29] Lee, S., Lee, S. R. and Kim, Y. An approach to estimate unsaturated shear strength using artificial neural network and hyperbolic formulation. Computers and Geotechnics, Vol. 30, Issue 6, 2003, pp. 489-503.
- [30] Fredlund, D. G., Xing, A., Fredlund, M. D. and Barbour, S. The relationship of the unsaturated soil shear strength to the soil-water characteristic curve. Canadian geotechnical journal, Vol. 33, Issue 3 (1996), pp. 440-448.
- [31]Gan, J., Fredlund, D. and Rahardjo, H. Determination of the shear strength parameters of an unsaturated soil using the direct shear test.

Canadian Geotechnical Journal, Vol. 25, Issue 3 (1988), pp. 500-510.

- [32] Willmott, W. F. Slope Stability and Its Constraints on Closer Settlement on the Mapleton-Maleny Pateau, Southeast Queensland. Geological Survey of Queensland, 1983.
- [33] Fredlund, D. G. and Xing, A. Equations for the soil-water characteristic curve. Canadian geotechnical journal, Vol. 31, Issue 4 (1994), pp. 521-532.

Copyright © Int. J. of GEOMATE. All rights reserved, including the making of copies unless permission is obtained from the copyright proprietors.